



US006767487C1

(12) **INTER PARTES REEXAMINATION CERTIFICATE (0231st)****United States Patent****Pearson**(10) **Number:** **US 6,767,487 C1**(45) **Certificate Issued:** **Feb. 15, 2011**(54) **PLASTIC EXPULSION PROCESS**(75) **Inventor:** **Terrence C. Pearson, Nantwich (GB)**(73) **Assignee:** **Cinpres Gas Injection Limited,
Middlewich, Cheshire (GB)**

6,019,918 A	2/2000	Guergov
6,354,826 B1	3/2002	Thomas
6,375,892 B2	4/2002	Thomas
6,576,170 B1	6/2003	Nunnery et al.
6,579,489 B1	6/2003	Thomas
6,602,460 B2	8/2003	Thomas et al.
6,716,387 B2	4/2004	Thomas

Reexamination Request:

No. 95/000,064, Dec. 6, 2004

Reexamination Certificate for:

Patent No.: **6,767,487**
 Issued: **Jul. 27, 2004**
 Appl. No.: **09/902,354**
 Filed: **Jul. 10, 2001**

(51) **Int. Cl.**
B29C 45/17 (2006.01)
B29C 45/76 (2006.01)

(52) **U.S. Cl.** **264/40.4; 264/40.1; 264/572**(58) **Field of Classification Search** None
See application file for complete search history.(56) **References Cited****U.S. PATENT DOCUMENTS**

4,208,368 A	6/1980	Egli	
4,824,732 A	4/1989	Hendry et al.	
4,923,666 A	* 5/1990	Yamazaki et al.	264/572
4,944,910 A	7/1990	Hendry	
5,028,377 A	7/1991	Hendry	
5,032,345 A	7/1991	Hendry	
5,069,858 A	12/1991	Hendry	
5,204,050 A	4/1993	Loren	
5,204,051 A	4/1993	Jaroschek	264/572
5,607,640 A	3/1997	Hendry	
5,824,261 A	10/1998	Berdan	264/572
5,885,518 A	3/1999	Hendry	

FOREIGN PATENT DOCUMENTS

CA	2125623	12/1994
DE	40 02 503	1/1990
DE	43 34 012	10/1993
DE	10128458	2/2003
EP	0628395	6/1994
FR	1145441	* 10/1957
GB	2158002	11/1985
JP	4-62118	2/1992
JP	06297522	10/1994

OTHER PUBLICATIONS


Dier and Goralski, Gas Assist Injection Molding, 2000, Bauer Compressors, Inc., pp. 71-91 and 93-104.*
 Rosato et al., Injection Molding Handbook, 2nd edition, 1995, International Thomson Publishing, pp. 79-80.*
 Rosato, Plastics Processing Data Handbook, 2nd edition, 1997, published by Chapman & Hall, pp. 191-193.*

* cited by examiner

Primary Examiner—Jerry D. Johnson

(57) **ABSTRACT**

A system and process for gas assisted plastic injection molding. The plastic material is injected into the mold cavity and the molding pressure is held for a period of time. Thereafter, gas is injected into the plastic material and the pressure is again held for a period of time. Thereafter, valve members are opened allowing plastic to be expelled into one or more secondary cavities, or to be expelled back into the machine barrel.



1
INTER PARTES
REEXAMINATION CERTIFICATE
ISSUED UNDER 35 U.S.C. 316

THE PATENT IS HEREBY AMENDED AS
INDICATED BELOW.

2
AS A RESULT OF REEXAMINATION, IT HAS BEEN
DETERMINED THAT:

5 Claims 1-16 are cancelled.

* * * * *